



Betriebsdruck max. 500 bar.

Grundbezeichnung		605-016	605-025	605-032	605-040	605-050	605-063	605-080	605-100
Kolben-Ø	(mm)	16	25	32	40	50	63	80	100
Stangen-Ø	(mm)	10	16	20	25	32	40	50	63
Druckkraft pro 100 bar	(kN)	2,0	4,9	8,0	12,6	19,6	31,2	50,3	78,6
Zugkraft pro 100 bar	(kN)	1,2	2,9	4,9	7,7	11,6	18,6	30,6	47,4
a	(mm)	60	65	75	85	100	125	160	200
b	(mm)	35	45	55	63	75	95	120	150
c	(mm)	40	50	55	63	76	95	120	158
d	(mm)	22	30	35	40	45	65	80	108
d1	(mm)	4	4	5	6	6,5	8	9	10
d2	(mm)	3	3	4	4,3	5	6	7	8
D	(mm)	11,3	11,3	11,3	13,8	13,8	17,8	17,8	17,8
g	(mm)	6,5	8,5	10,5	10,5	13	17	21	25
o		M6x12	M10x15	M12x15	M16x25	M20x30	M27x40	M30x40	M42x60
SW	(mm)	8	13	17	22	27	36	46	55
L1	(mm)	40	44	50	54	65	72	85	90
L2	(mm)	6	7	10	10	10	14	14	15
Masse Hub »0« (kg)		0,59	0,87	1,37	1,98	3,33	5,74	11,16	18,33
Gewichtzunahme pro 10 mm Hub (kg)		0,14	0,19	0,26	0,33	0,45	0,71	1,16	1,83

Hubvarianten für		605-016	605-025	605-032	605-040	605-050	605-063	605-080	605-100
Hub 1	(mm)	16	20	25	25	25	30	32	40
Hub 2	(mm)	50	50	50	50	50	63	80	100
Hub 3	(mm)	100	100	100	100	100	100		

Bestell- Grundbezeichnung + Hub in mm = Bestellnummer
beispiel: 605-050 + 025 = 605-050-025